



ADE3TRGS455LW01

A proven performer

Speed Queen® dryers are designed, tested and built to deliver 25 years of commercial-grade performance in your home. Featuring customizable drying cycles, sophisticated airflow patterns, and advanced moisture sensing to deliver consistently superior results and efficiency. So you can reduce your dry times, eliminate unnecessary drying, lower your utility bills and protect your clothes.

Perfected drying


Through special drying cycles, a flawless Axial Airflow pattern and advanced moisture sensing, you can eliminate excessive drying and save money on your utility bill. If you want durability, innovation and perfectly dried laundry the first time, you need a Speed Queen dryer.



Specifications

Speed Queen Home Retail Dryer

ModelADE3TRGS455LW01General detailsControl3 Cycle MechanicalControl locationRearActuationNoneDrumCapacity kg10,5Volume I198PowerMotor power kW0,25Voltage220-240/50/1CabinetCylinder FinishGalvanized		
Control3 Cycle MechanicalControl locationRearActuationNoneDrumCapacity kgCapacity kg10,5Volume I198Power198Motor power kW0,25Voltage220-240/50/1Cabinet1000000000000000000000000000000000000	Model	ADE3TRGS455LW01
Control location Rear Actuation None Drum Capacity kg 10,5 Volume I 198 Power Motor power kW 0,25 Voltage 220-240/50/1 Cabinet	General details	
Actuation None Drum 10,5 Capacity kg 10,5 Volume I 198 Power 0,25 Motor power kW 0,25 Voltage 220-240/50/1 Cabinet	Control	3 Cycle Mechanical
Drum Capacity kg 10,5 Volume I 198 Power Motor power kW 0,25 Voltage 220-240/50/1 Cabinet	Control location	Rear
Capacity kg 10,5 Volume I 198 Power 0,25 Voltage 220-240/50/1 Cabinet	Actuation	None
Volume I 198 Power 0,25 Voltage 220-240/50/1 Cabinet 1	Drum	
Power Motor power kW 0,25 Voltage 220-240/50/1 Cabinet	Capacity kg	10,5
Motor power kW 0,25 Voltage 220-240/50/1 Cabinet	Volume I	198
Voltage 220-240/50/1 Cabinet	Power	
Cabinet	Motor power kW	0,25
	Voltage	220-240/50/1
Cylinder Finish Galvanized	Cabinet	
	Cylinder Finish	Galvanized
Color White	Color	White
Door type Solid	Door type	Solid
Connections	Connections	
Electrical requirements 220-240/50/1	Electrical requirements	220-240/50/1
Transport data	Transport data	
Net weight kg 57	Net weight kg	57
Shipping weight kg 62	Shipping weight kg	62
Dimensions HxWxD mm 1086 x 683 x 711	Dimensions HxWxD mm	1086 x 683 x 711
Packed dimensions HxWxD mm 1156 x 775 x 826	Packed dimensions HxWxD mm	1156 x 775 x 826
Packed volume m3 0,74	Packed volume m3	0,74



Dimensions

	mm
А	683
В	711
С	1086
D	392
E	597